



G01A-332

750 MV THERMOPILE GENERATORS

Provides power for 750 millivolt control systems.

FEATURES

- For replacement of similar screw-in type generators and E31-12 pilot burners
- G01A-332 has 36 inch armored cable leads with split-spade terminals
- PG9 adapter included with each G01A-332
- 101934F32 / 101934R32 designed for use with PG9


SPECIFICATIONS

Nominal Voltage 750 mV
 Maximum Hot Junction Temperature 1400°F
 Maximum Cold Junction Temperature 650°F

750 MV THERMOPILE GENERATORS

MV OUTPUT	LENGTH	FIBERGLASS CABLE LEADS	ARMORED CABLE LEADS	PG9 ADAPTER	CLIP INCLUDED	CONNECTOR TYPE	MODEL NUMBER	ITEM NUMBER
750	32	✓	—	—	—	R Bushing	101934R32	101934R32S2
750	36	—	✓	✓	✓	F Spade Terminal	G01A-332	G01A332S1
750	36	—	✓	—	✓	F Spade Terminal	G01A-502	G01A502S1
750	36	✓	—	✓	✓	F Spade Terminal	G01A-512	G01A512S1
750	36	—	✓	✓	✓	F Spade Terminal	G01A-132	G01A132S1
750	32	✓	—	—	—	F Spade Terminal	101934F32	101934F32S2
750	36	✓	—	—	—	F Spade Terminal	G01A-501	G01A501S1

* Indicates Canadian Model Number: Call 1-800-305-6953 to order.



PG9A27JTL22

PG9 SERIES 750 MV GENERATORS & PILOT BURNERS

Provides a pilot flame for igniting gas burners while generating millivolt output to operate gas valves and relays.

FEATURES

- Single blue flame burner for quiet operation and maximum flame stability
- "Snorkel" primary air path incinerates dust eliminating linting problems
- All models provided with orifice base fittings for Natural and LP
- Flame ring surrounding generator ensures high output and extended generator life
- High temperature stainless steel generator cover

PG9 SERIES 750 MV GENERATORS & PILOT BURNERS

HEAD TYPE	PORTING	ORIFICE	FITTING	MODEL NUMBER	ITEM NUMBER
Channel Type	90° right & 90° left, 3/4" head width	0.022	Includes extra base fitting for LP gas application (less ferrule and nut)	PG9A27JTL22	PG9A27JTL22S2
Cobra	90° left	0.020	Includes extra base fitting for LP gas application (less ferrule and nut)	PG9A41JTL20	PG9A41JTL20S2
Cobra	90° right	0.020	Includes extra base fitting for LP gas application (less ferrule and nut)	PG9A42JTL20	PG9A42JTL20S2