

# A/C Scroll Models

**Compressor Family Series**  
 Either a number or a letter established for each product model.

**Modulation**  
 D - Digital  
 DU - Digital Uneven Tandem  
 DT - Digital Even Tandem  
 H - Horizontal  
 S - Two Step  
 T - Even Tandem  
 U - Uneven Tandem  
 V - Variable Speed

Compressor nominal capacity at rating condition to two or three significant digits.

E - 3MA Poe Oil

Phase	Description	Code
1	Capacitor Run - Permanent Split Capacitor	P
3	General 3 Lead Single Voltage 6 Lead Part Winding (575 Volt)	T

**Product Variations**

- 130 indicates a standard compressor and component parts with molded plug connection.
- 230 indicates a standard compressor and component parts with quick connect terminal.
- 250 indicates standard compressor and component parts with screw on terminals.
- 260 indicates standard compressor and component parts with quick connect terminal and rotolock valves
- 700, -900 series indicates standard OEM and wholesaler service.
- Other numbers designate variations

X X X X X X X X X - X X X - X X X

Code	Refrig.	Description
P	R-410A	High Temperature Ultra High Pressure
R	R-22/407C/134a	High Temperature
Z	R-22	High Temperature Tandem Configuration

**Model Variation**  
 A number or a letter, assigned to indicate different model types within any one family series.

**Capacity Multiplier**  
 K: 1,000  
 M: 10,000

60 Hz.	50 Hz.	Code
208/230-3	200-3	C
460-3	380/420-3	D
575-3	-	E
265-1	220/240-1	J
265-1	-	Q
-	220/240-3	R
208/230-1	200-1	V
Misc.	Misc.	X
200/230-3	200/220-3	5
380-3	-	7
-	380-3	P
-	220/240-1	Z

Type Protection	Code
Internal Inherent Protection— One Protector Use with Contactor (Single or three phase)	F
External Electronic Protection— Kriwan Module (Three phase)	W