# GO Real-Time XL Tracker

Temperature, location and security

#### **Global Visibility and Protection for Extended Shipments**

Extended battery life provides full coverage for your products on the road, in the port and out on the water. When your ship leaves port, the GO Real-Time XL keeps track of the temperature. Every time the ship nears port, the unit automatically connects and uploads data before the ship reaches the docks. Rest assured that visibility to temperature and location data will be available despite the ongoing transition in the cellular technology industry.

The GO Real-Time XL Tracker senses light when doors are opened and alerts you when your products are at risk on the road.

#### **Oversight Dashboard & Mobile App**

Comprehensive and automated reporting is provided through the Oversight Dashboard and the Oversight Mobile app. Data is encrypted, providing security as it moves to the cloud. Information is at your fingertips while you are on the go with Oversight Mobile. Check status and create shipments direct from a phone or tablet. View current maps, graphs, and charts of key shipments including temperature, security, and location details. Shipment summary reports include additional details such as device serial number, trip name and duration, mean kinetic temperature, and time above or below range. The Oversight Mobile app is available in English, Chinese, Spanish, Russian, Italian, German, Portuguese, Turkish and French.





An easy-to-use system to monitor shipments



Extended battery life to cover international shipments



Global visibility with email/text alerts



Access to temperature reports before final delivery

Recycle with GO GreenSense™



#### **Technical Specifications**

Battery: Cellular:	UN38.3 compliant 850/900/1800/1900 MHz Quadband
Cellulal:	GSM/GPRS
Certifications:	FCC, PTCRB, CE, Anatel, IFETEL, CNC, ICASA, EAC
Device Storage:	Optimal: Below 20°C and 60% RH
In-Use Life:	Up to 45 days operation at 0°C and up to 25 days operation at -20°C with 60-minute location and temperature measurements reported at 60-minute intervals
IP Rating:	IP54
Light Sensor Sensitivity:	±0.5 Lux, minimum detectable 1.0 Lux
Oversight Dashboard:	Emerson.com/Oversight
Recycling Options:	GO GreenSense™ Program
Size:	3.07 in x 2.06 in x 1.31 in (78 mm x 52 mm x 33 mm)
Shelf Life:	Shipped with a minimum in-use and shelf life of approximately 6 months. Please check the "Activate By Date" on the product box and follow a first- in-first out process.
Temperature Accuracy:	±0.5°C (0.9°F) typical between -20°C to 60°C (-4°F to 140°F)
Temperature Range:	-20°C to 70°C (-4°F to 158°F) operating environment.
Weight:	136 g (0.30 lbs)



Oversight Mobile Summary Report



Download the Oversight Mobile app



Oversight Mobile Map Detail

## **EMERSON**. GO Alert Notification

**Event:** Alert! The temperature is too low. Immediate action is required to prevent damage to your product.

GO #: 15000845 Trip Name OR1338343 PO 0266-8530262-3895 Location: IA-27, Riverside, IA 52327, USA



Email Notification

**Contact Information** 

+1 (877) 998-7299 CargoSolutions@Emerson.com

TX2-TL00.DS.Rev1.1120 Emerson and GreenSense are trademarks of Emerson Electric Co. or one of its affiliated companies. ©2020 Emerson Electric Co. All rights reserved. Emerson.com/Cargo

### EMERSON. CONSIDER IT SOLVED