

Our Industrial Solenoid Valves are approved for use with the fluids utilized in secondary loops such as Ethylene and Propylene Glycol and Tyfoxit. The recommended seat material is Buna-N.

In addition to air, water and steam, the following is a listing of secondary loop fluids that are compatible with our valves:

These valves referenced above are as follows:

202CB	211CA
203CA	214CA
204CD	222CB
210CA	314UB

Fluid Name	Manufacturer
Ethylene & Propylene Glycol	Various
Tyfoxit	Spauschus Associates (Distributor)
Siltherm XLT	DOW
HFE	3M
Dowfrost	Dow
Pekasol	Unknown
Dynalene	Dynalene

When ordering valves for the above stated application, be sure to mention the Elastomer Code "B" which designates Buna-N.

Nomenclature example: 222CB 1/2 B 1/2 B

2	22	C	B	1/2	B	1/2	B
Valve Type 2 = 2 Way 3 = 3 Way	Product Group Two digits to Define Group	Form of Flow C = Normally Closed O = Normally Open U = Universal	Design Series Letter will be advanced to identify product changes	Pipe N.P.T. 1/8" thru 2" GS indicates non-standard	Body Material B = Brass S = Stainless Steel T = Stainless Steel with Silver Shading Band	Body Orifice 3/65" thru 2"	Elastomer Code B = Buna-N